



FIG. 1B



																			-
\Box		Ĺ,	\int																
		-									•								
固		-				· 						·		1				- '	Ш
		١	×IO		_E	<u> </u>	Τ			[0]			P	7		•		-	
			Ē	1	2 <u>0</u>				-) j	9						
		1		5	X						cv m	d mper	See 1/0						
		ı		ations			1	-		Ξ		-10	11				,		$ \bigcup$
				ig.	影							<u> </u>	턡		╟╜				
1. 1		ı		8	<u>ء</u>					Max	1 1 9999	20 20 20	嵳		L	L.		-	
		-			<u> </u>		Ь			je j			ਿਲ ਲ		占	日			
		1		ol ass			П		څ ۱	Manufacturer	Numatics Numatics Namco		5						
			1	contr	වි ව		Ц	88 5	鼍	Man	Nan		ğ Ç						
				es Se			E,	i i	賣			-	io K						
				des			Salai	Š	288		erter		뽈						
		ı		λ Ha				8 2	탏	٥	5 e 5		5 29						
		ᅰ			=		Control AssemblyCatalogID	훙	8	Role	S S S	٦	- E			Ċ			
	윤			o goli	<u>s</u>		B	1 2 S	훓		main control safety valve air-motion coverter	Clamp	흝						
	_	븼		cata		nents		2. € 5. €	喜				ج ق						
	Window			achine resource database has two parts. A catalog or library that describes control assemblies, configurations of	hat perform distinct control tenctions, that can be used in a machine resource description and a set of tables used to Assemblies with Physical Components	iber of catalog entries with Physical Components		This is labled as "safe" clamp because it needs to have two air valves	휷			00	the 1/0 associated with a component, click at the begining of the row, and then click on this button						\mathbb{H}
	≥	흶		04	hat perform distinct control lanctions, the Assemblies with Physical Components	<u>Ş</u>	l	芸を	툁	2	doublesolenoid singlesolenoid Cylindicator		ē						
	8	50		has t		E			' 홍 콧	Subtype	doublesolen singlesolenc Cylindicator		8	ë					H
1	H'	- 16		base		E S			physic	1	9 % %		章	ig Eag	•		E		
	Records	Δ -		data		altie e			를		000	D D	ated	5	•		Jans		П
	- 11	- 0		Source	E X	89 88	ង	او	<u>ss</u>				388	會			ents		
	Format	1		e e		20	5	cheadclamp	5.	ent Type	j	npoody	2	this assembly can perform:	1		omponents subform		
	Insert	- -		nachi		age.	ES F	를 18	owing	틸	airvalve airvalve aircylinder		ᆴ	s this	1 1		Sep		Ш
-	11.	耳		The m		Total num	Previous & Next	safe-bu	The following is a list of the physical components that make up a control assembly of this type:	Elem	2 2 2	Ciar	58 98 98	Actions	oben Open	Close	Cell Me		
8		9			Components in	Ľ			Æ		Δ	. •				<u> </u>	Main Men Structural		Н
Microsoft Access	Edit View	ᆁ		'	3						•) (C) (C	3000		
joso			نــــ								Ш			<u> </u>					H
送	≝																		
	L	4						·											لسا

FIG. 3








FIG. 5A








FIG. 6

-1G. 9




FIG. 1(




FIG. 1.

FIG. 12




FIG. 1.

4 š (Z)(E)(-) File Edit Draw View Database Manage Options Tools Reports Help Help Activity Tools Dumps

Pin 5507A

Coalor 550

Coalor 550

Coalor 551

Camp 250

Clamp 450 Safety Gate Project Build 0 • Add Engage Disengage ClocatorSet Command Command Command Command Viev Control
Contro O PinSet O 1stPi D 2nd 02ndP 0 3rd 0 4 th

FIG. 18

FIG. 16









FIG. 17



















































































FIG. 48




FIG. 49A




FIG. 49B






FIG. 5(

FIG. 51


SE	EQ	
ĖNA	BLE	-+()-+
! "	N +-1 -++	MAP #B1
1	ALWAYS TRUE	MAP #B2
1 1	F H +-1 -+	MAP #L1
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	E G	MAP #L2 -+()-+
1 1 1 1	j L +-1 +-1 +	MAP #L3
1 1 1 1	K +-1 1	MAP #L4 -+()-†
1 1 1 1	1 K	MAP #L3
! ! !	B D M +-11	MAP #R1
: : :	A C	MAP #R2
1	F H +-11	MAP #R3
; { { }	E G +-1	MAP #R4
	J +-11	MAP #R5
• • • •	K +-1	MAP #R6
<u> </u>		







Enterprise ControlsTM
Designer Studio
This computer program is protected by
U.S. and International copyright laws as
described in Help About
Copyright © 1998 Allen-Bradley Company

FIG. 52








		1 1		[X][D]=)	<u>E</u>
	- 1	Tools Window	Help	- 5506	
Control	ol Assembly hical Tim	iming Diagram			
	A IAM98 Workce	▲ IAM98 Workcell Timing Diagram		□ Operator	
1_sw1	1	· •		Cycle Time	
	Resource	Activity	<u> </u>	92.0 Secs	
	Pin 2504A	Fixture			
	Pin 5506A	Fixture	# 12 E		
	Robot Gripper	Load			•
		Fixture	· .		
		Fixture	***		
		Fixture	\$\$\$		
	Clamp 5508B	Fixture	***		
		Fixture	XX.		
	Clamp 5516A	Fixture		+	- 5820
	•	Fixture	22.		
	Clamp 3514A	1	র		
	Clamp 3514B	Ī	- X		
	Fin 550/A	Ī	24.F.		
	Locator 2501A	T	îč.		
	Locator 22U3AR	Ī	1		
		Ī			
	Clamp 3202A	Ī	133		
	Ulamp 3314AK	rixiure	***	0	
اما	٥			4	
	Control Bar Chart	art			— 5510
	IAM98 Workcell Bar Chart		配置 Physical 配置 Programmable 回いfual 医型Conditional	rtual 🖾 Conditional 鱼	
	Control Assembly	S	5531	Cycle Time	
		Γ		92.U.Secs	2830
				,	
	- Control Assembly	bly Conditiona	5529 - 5527		
				8	
	٥			4	
ı					

FIG			5562		
	医器 Robot こう Operator Add Control Assembly Type	part-present NachiSA160-controller Safe-bulkheadclampset pinset locatorset dumpset	5564		5558 5574 Beck Ned Finish Cancel P
nw Heln	EEEE Mechanical		Control Assembly T safe-builheade	5576 Crate Wind Disgram for the assembly Crate Wind Disgram for the assembly Crate Wind Disgram for the assembly Crate all available Disgrades for the assembly Crate Discoursentation for the assembly	
Project Build Tools Window	Mechanical Timing Diagram AM98 Workcell Timing Diagram Resource Activity Fixture	5502A 5506A ot Gripper np 2506A np 4502A np 5508B np 5509A np 5516A	3514A 3514B 5507A 5501A 5503AR or Loader 5505A	Control Bar Chart A IAM98 Workcell Bar Cha	Control Assembly
View Add	1 PP 1 P	Clamp Clamp Clamp Clamp Clamp Clamp Clamp	Clamp 5509A Clamp 2507A Clamp 2506A Clamp 5505A Clamp 5508B Clamp 5514AR Clamp 5501BR Clamp 5501BR	, 1812299 5	DumpSet

F	त	T	Τ	वा				=		-			=	=	=	=				=	==		7	Þ	T	4	T		===		T	ন
C	1					1	New	2	Cancel							I						\Box		П	al.						5	
H	4	ı		_			کا									\int	Γ	Γ								ţ				Cancel	Ш	
				age	≥	1 :	2	<u>e</u>	oset																5564	5				H	Ш	
				Estator	冒		7	intro	lam)		_		_	Page 4		
					Ass	1		Д	adc															ſ	ጎ			査		F	Ш	
			l		B		Sen	416	Khe	-	ن ة -	<u></u>								-			≩	.			3		/			
				8	Add Control Assembly	3	Dart-present	VachiSA160-controller	safe-bulkheadclampset	pinset	ocatorset	aumpset	•			lF	\vdash						Age			~	A	可可	8	ğ	Ή	
	ŀ	l	l		Be	2		Na	S.	٥	<u>ප</u> ු	<u> </u>				$\ $							Salta			5578	₽ E	for the	5558	Ш	Ш	
				配置 Mechanical 配理Robot		T	H	1	E	E	287	25.0	**	33	23		ର୍	;;;;;		ë		nempset 1	Specify name for the new Control Assembly			j	Ę	Create all available Diagnostics for the assembly Create Documentation for the assembly			H	
				hau			Ц	1	A.Y				4			L			g 2	Control Assembly Type:	and the second		<u>5</u>	-			S S	off evalls Occumen			П	
				Mec					77.77										- Slep 2 of 5	d Asse	1	Š	A agr		SUCRUMB!		120	įį			Ш	ı
	무임					Į.	3 <u>0</u> 2	3 2		Н	Н	+	\dashv	\dashv	-		Н		Ę	3			Š	_	_		030	80			H	
				E			П	\overline{T}	$\overline{\Gamma}$		$\overline{\sqcap}$	T	٦	٦					Control Assembly Witzard	ſ		4	ξ	٦							Fi	
	I≩			agrai		<u>.</u>	<u>e</u>	믿	,	စ	9	2	9	ဍ	9	9	9	9	Assem	ŀ	\prec	, \	\geq	Н								
	Window		Diagram	ă		Activity	Fixture		100	Fixture	Fixture	Fixture		Fixture	Fixture	Fixture	Fixture	Fixture	8	L		2		_]								
	>	11	Dia	nin		Ì	T	T				T	T	ī			\exists	司	1	T	T	T		7	T	E		ſ	$\overline{}$	1	i	
	Tools		iming	Ē														-				ı			닕	IAM98 Workcell Bar Cha		칅		音	1	
	۲			r Se					2		6A	al s		8	S	×	₹	땆	₹	A.6			5514AR		පි	9		E S		Sem	ı	
	멸		ខ្ល	%		۵	2504A	55067 55067	Robot Gripper		2506A	3	2508B	5509A	5516A	22	3514A	35148	330/A	ocator 5501A		Clamp FROSA	22.5		Control Bar Chart	Ş		Control Assembly		Control Assembly	1	1
	Bried		Mechanical	86		Resource	25	35	B		Сашр	Claric Control					Samp						Clamp	L	喜	8		읦			۱	L
	ect	П	ğ	IAM98 Workcell Timing Diagram	i	E	E 6	<u> </u>	8	3	ဝိ	Ö	3	ğ	Š	ဝိ	ဝိ	င်း		5 3	36	3E	30	-	පි	M		႘		႘	J	₹
	Project			٥													I							+-		9					Þ	
		П			₹?	74	<u> </u>	% 2							•									1								4
	Add				. PP1_sw1	?. -	22.5																				بيه	Set				
		$\ \ $	8		5 Z	5	sor PP2_sw1	<u>.</u>										_			_ 0	Ľ C	ح مح				<u>e</u>	ğ				
	View	Ц	Resou	n ~	ProximitySens ProximitySens	xture Nest 2	ProximitySenso	Šens Šens	Robot Welding 04		14A	3514B	5516A	5516P	35	3 8	300WA	2507A	5500A	SOCON FINANCE	33000 55144	¥ 7 6	5503B		rces	Ses	Sont	OSafe-BulkheadClampSet				
		ď		2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Z Ž	8	É	- ProximitySenso	말듣	ase	ည်	35	55	35	750					מ מ מ					Soul	E S	ဒြို့	x Fea	ĕ			
	뎚			≥Z = 2	Proxi	و ک	Š		5≷ 5 5	<u>ا</u> و	amp	뼯	amo	1 6			C Sallo	Claring	2 E						E	A g	SA	굨.	हैं डिप्र	pSe		
	File		Mechanica	workceii IAM98 D Fixture Nest 1	تـــ	Fixture Nest	—	֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓	2 2 2 2 2 2 2 2	E	20	O Clamp	O Clamo		֓֞֞֞֞֞֞֞֞֞֞֞֞֞֞֞֓֓֓֓֞֞֜֞֓֓֓֞֞֞֓֓֞֞֓֓֞֞֞֜֞֞֞֡֞	5 č	3 c		ה ה	3 C	3 C		30		Control Resources	Control Assemblies	덡	Safe	C LocatorSet	DumpSet		
	正		≥!	0 ۶		0				0														V	ರ	ರ	0	őc	0	ō		F

550,



<u> </u>		- 5607	
Window Help	Registration	Fixfure Fixfur	
Project Build Tools W	Resource Pin 555 Pin 5	Clamp 55088 Clamp 5508A Clamp 2507A Clamp 3514A Clamp 3514B Pin 5507A Locator 5503AR Operator Loader Clamp 5505A Clamp 5505A Clamp 5504A Clamp 5505A C	▼ A
File Edit View Add	Danica Cell IA Proxi- Proxi- Proxi- Dot Gri Clamp	5516A 5516B 4502 5509A 2507A 2507A 2506A 5503B 5501BR 5501BR 5503BR 5503BR 5503BR 5503BR 5503BR 5503BR 5503BR	•

		_	_						_	-			_	_	=					-		Т		-			=		T	
	Heip		配置Mechanical 配置Robot このperator	Cycle	92.0 Secs	Add Control Assembly		누		Safe-bulkheadclampset Cancel			nacillon Se	***	50% ₹			***					紹子 Physical 医型 Programmable 区型 Virtual 医型 Conditional	Cycle Time		***			J. 6830	Δ.
o the transfer of the transfer	Project Build Tools Window	IMechanical Timing Diagram	▲ IAM98 Workcell Timing Diagram		Resource Activity H		Pin 5506A	ot Gripper	Clamp 25064 Fixture	4502A	5508B		5516A	2507A	Clamp 3514A	Ī	ator 5501A		or Loader	Clamp 5514AR Fixture		Control Bar Chart	A IAM98 Workcell Bar Chart EZB Phy		ssembly	Istciamps ext	Control Assembly		. 6820	0
10 m	View Add	Mechanical Resources		SOIS	Proximity Sensor PPI_sw2	_	L Proximitý Sensor PP2_sw2	Robot GripperO5	o Fixture Easel	Clamp 3514A	Clamp 3514B	Clamp 5516A			Clamp 5509A	Clamp 2505A	Clamp 5505A			Clamp 5501BR	Ciallip 22036	Control Resources	Control Assemblies 6840	= =	Distolamps	D Retract		a mode-selector 6810	D cycle-selector	▼

				•				
FIG.			-				- 5830	
Project Build Tools Window Help	Mechanical Timing Diagram 磁圈Mechanical 磁器Robot こOperator	Resource Activity Heronomy 2504A Eixture Right Pin 5502A Eixture Right Pin 5506A Fixture Right		2507A France 3514A France 5507A France 5507A France 5501A France 5501A	AR Fixture er Load A Fixture 4R Fixture		Control Assembly Request + 7001 5531 Cycle Time 1stclamps 1stc	
File Edit View Add		ProximitySensor PP1_sw1 ProximitySensor PP1_sw2 Fixture Nest 2 ProximitySensor PP2_sw1 ProximitySensor PP2_sw2	Robot Gripperus Robot Welding04 C Fixture Easel C Clamp 35148 C Clamp 35168 C Clamp 55168	Clamp Clamp Clamp Clamp	Clamp Clamp Clamp Clamp	Control Resources Control Assemblies Control Assemblies Control Assemblies Control Assemblies	Case - Bulkhead ClampSet - Gistelands - Gist	
			-	6940			6911 -	

L	_								ų	2																								
								5548	2722						5820												000	2830						
٠						-		12							Ī						- 1			ন_	1	F	<u>_</u>							
		国	New		Cancel	•		T	V			h			\dagger	F	F	AV:	25.0	1.50 E	e la	K M	150	H_	1	필	ر ا	4	H	₹ ₹		\mathbb{H}	0	Δ
H								floor			¬	П			7	Г	1				T	T				<u>@</u>	Ë	92.0 Secs	***					П
		賣	Z De			350																				8	Cycle Time	. 92.0						
		Asser	Àqu			ancia											(A) (基本) (基本) (A)									taal								
		ontro	Asser	part-present	SAID	pare Durniegucialipsel	13.0	Se :	;			Ц	3N	3.5	X¥.	N.V.		Ц		1	1	1							Ы					
		Add Control Assembly	Control Assembly Type	part-p	Nacu	Dincet	ocatorset	dumpset													T					紹 Physical 紹 Programmable こういれual こっていれitional								
			7.0			88	37	25	1	83										\downarrow	${\downarrow}$	+				gramn)		25	\exists		4		
				╁	$\ \cdot\ $	H	+	+	+						\dashv				-	+	+	+	H			200 Po			H	-	l	1		
	윤			1		Ц	1	1	1						_					1	\downarrow	1	\square			ical				4	ŀ			
			П	T	Π		Ī	Ť	Ŧ	П								g)	2	2	واي	يو ايو	9]		a Phy		_	$\overline{\prod}$	$\overline{1}$	a B	$\overline{\ \ }$		
	Window	E E	Fixture		Fixture	ixture			E SE	Fixture	Fixture	gg	Fixture	Fixture	Fixture	Fixture	Weld	InFixture	UnFixture	n Fixture	In First ure	Fixture By the	Infixture	H		E 34		ednes	ext	힏	Conditiona	l		
1 1	1	Diagr		-	Ш		<u>-</u>		Ë												T	T				Chart	1	<u>ح</u> ا	П	ī		ĭ		
	Tools	iming Diagram									œ			ڀ	≆	æ									hart	IAM98 Workcell Bar Chart	•	in y		l	d m			
1 1		且	9		960 V		Г	### ##	5507A	Locator 5501A	ocator 5503AR	Operator Loader	5505A	5514	5503BR	5501BR	elder	2506A	4502A	Clamp 5508B	15000 FEET	55168	5505A		Control Bar Chart	Norko		Control Assembly	8	S	Control Assembly			
1 1	Build					Complete				ocator	ocator	De la company de	Clamp	Clamp	Clamp	Clamp			Clamp	all a		a la	Clamp	L	ontro	M98 \		ontro	stclamps	stclamps	onto			Н
	Project					s Con		Ė	<u>- 4</u>			의 -	ပ္	ပ္	<u>ာ</u>	<u>ပ</u>	<u>~</u> 1	<u> </u>	<u>or</u>	<u>SK</u>) [- P	19	2	3	¥ ₹		~ 		<u>=</u>	T	_	•	V
		ŧ	ĕ.			urce											•							٥							,			٥
	Add		ICal		-	Resource																		П				ביבו						
	_ <u>≷</u>	Font	меспапісаі уіем			Control			Ω≥	5	4	ξ 🗖	9 -	₹ 9	2 2	<u>~</u> 1	8 6	X	6 A	5A	88	5514AR	5501BR		Ses	es	Sontrol	<u> </u>				_	8	
IГ	I View			ត្តត	ام ا	Nest CO	Ŀ	<u>ٔ</u> ا	Robot GripperO5 Pobot WeldingOA	Fixture Facel	2517	151		3310A			5509A		2506A		D 5508B	551			Resources	Control Assembiles	ONachiSA160-controller	MDS	end	Tacı	Şet	a mode-selector	D Factory Service	
	텶	Mechanica	Work Cel			ure N		9	© ₹	1						Clamp	Clamp	Clamp	Clamp	Clamp	Clamp	Clamp	Clamp		Control R	In-Par	Schist P. B.	1500	o Extend	D Pinset	O LocatorSet	2450	Sctory	
	<u></u>	Wec	≯ ‡	ž—		OFixture		, د	~	<u>.</u>	֓֞֞֞֜֞֜֞֜֞֜֞֜֞֜֞֜֜֞֜֜֜֞֜֞֜֜֜֓֓֓֓֞֜֜֜֓֓֓֡֓֜֡֓֡֡֡֡֓	י כ) (<u> </u>	0	ō	ō	ā	0	0	0	0	ō	ខ្ល	36		;0 !		<u>6</u>	<u>ک</u> ز) E	O F.	V


•		
	5707	
		 1
Nanical Timing Diagram RESENTATION Propertion Cycle Time 98 Workcell Timing Diagram Cycle Time 2504A Activity Cycle Time 5502A Fixture Matwiss 5505A Fixture Matwiss 5505A Fixture Matwiss 5505A Fixture Matwiss 5508B Fixture Matwiss 5508B Fixture Matwiss 5509A Fixture Matwiss 5508B Fixture Matwiss 5506A Fixture Matwiss 5506A Fixture Matwiss 5506A Fixture Matwiss 5506A Fixture Matwiss Fixture Matwiss Matwiss Fixture Matwiss Matwiss Fixture Matwiss <t< th=""><th>Request Solutional EZB Programmable Conditional Solutional Solutio</th><th>Resources it controls 2107 5529 5527 5705</th></t<>	Request Solutional EZB Programmable Conditional Solutional Solutio	Resources it controls 2107 5529 5527 5705
_ 4		
Mechanical Resources WorkCell IAM98 © Fixture Nest 1 ProximitySensor PP1_s ProximitySensor PP1_s ProximitySensor PP2_s ProximitySensor PP1_s ProximitySensor PP2_s ProximitySensor PP1_s ProximitySensor PP2_s ProximitySen	Control Resources Control Assemblies Control Assemblies Control Assemblies Control Assemblies Control	Past-Present and the Mechanical
	2508	
	Nechanical Hming Diagram Alambas Workcell Timing Diagram Resource Activity Sor PP2_s Sor PP2	Control Resources


Project Build Tools
IAM98 Workcell Timing Diagram Resource
Pin 2504A Pin 5502A Pin 5506A
Clamp 55168 Clamp 55168
Control Bar Chart
△ IAM98 Workcell Bar Chart
Control Assembly
Zadpins Gripper-Controller
dumos
2ndclamps
locators
Operator-Station
4thclamps
Welder-Controller
1stclamps 3rdclamps
2ndplus 2
locators
• dumps
V
ical Resources it controls

													_	 -															,	
×		4	T								1	1	1	1		T												Þ	L	
同			1		** Y	-	П	I	I	П		۵	1			П		\perp			\perp	\Box		_	14	44	4	38	Δ	
HI		•	יין פ	\Box				\perp	L	П		╟╴	1	2	<u> </u>	ָּר בּ		4-	Н	H	+	┦┤	\dashv	-	_	S (2)	242	Н]
				1				- 1		il	-	H		15	<u>: </u>	Sec		1						3				Н		1
111		5 F		1				-			1	1		Į	; 	Ľ		1			ı			Š						l
		<u>ج</u> ج	<u> </u>	1			H	- 1	1		.	ll	1	Į	쁫	97.0					I									
111		e S	9 C 7 C C C 7 C C C C		ما اند		1	-	1		1	II			Ovcle Time	þ					1			S					l	İ
		Operator	7 T	M			l	-		1 1	ı	ll	1		J ~	Τ					1			F				П		1
		A	- 1					- 1	1	11		ll	1	1 7	i			1			1			Ŋ					i	l
1		كا	- [1	1	ll	-	II	1	E	3						ı	H	ı	Š	4				l	ĺ
111		∺	- 1					- 1	1.		- 1		1	ΙŽ		- 1		1			1			SEANSE ANTANEZ ANTANAN	1	13		ı		1
1 1 1	11	既遇 Robot					Н		+	Н	+	Ħ	1		1	- [1	П		1	П	13	3					1	
1 1 1		≅ .		П			П	\top	1	П		11	1		•	١		\top	П	П	Т		Т	Т	П	::-		П	1	ļ ·
1		20			12 Y		H				- 1			置				-	П				-	1	11		1		l	l
111				H				ı				11		1 2	}			1			1	ANARAS.	1	•	11		1	.		l
111		ā					Ц			Щ	4	IJ.		ΙĒ		ı	H	4	132		-		4	- -	₩	11	- -	Н	١.	
111		<u>.</u>	ľ			4		स ह	***	4	<u> </u>	H	l	1 2	Di	- 1	H	-		53 (32	1	-	╁	++	+ +	- -	Н	1	
111		ğ			: :		X	_ _					1	١٥		- 1	且		Ш		┸	Ш		\perp	Ш			Ц		l
111		医型 Mechanical	l		· £	- 24	П	T	П	П	Т	N			i	1	1	100							11		1			l
111		ž	- 1								1							ä		١	ŀ		١.		11			П		
니의		83	- 1		-	1 2				Ш		U		ल	į	-		<u>¥</u> _	Ш	Ц.	┸	Ш	_	1	Ш	11		Ц		
문	'	1 23	İ	83	建設		\Box	$oldsymbol{\bot}$		Ш		4-	1	Si	;	1	23		Ш		ㅗ	Ш				1:1		Ц	H	
	11	_			.v.	П	П	T	T	П	Т	rl 💮	ļ	(変数 Physical (変数 Programmable (同) Virtual (国)				e l	П	Т	T		Т	Т	П			П		
	11	₽			-		H	1			ı				1			ogo-Cycle				oad-Part	- 1	1						
≥	11	ğ	-≤-	Fixture	Fixture	2	9	Z Z	9	Xinre	일일		Ì	B		Request	l C	1		-										
		$\ddot{\Xi}$	Activity	冒	킔	80	xture	z de	xture	륁		H				킁		ă	닏	닔,	باي	18	닔	χ δ	힏	過	<u> </u>	ē		
Window	Timing Diagram	Workcell Timing Diagram	Ş		4	13		<u> </u>	Œ		퍄	4		یا		జి	ह	o š	ĕ	ह्य	Š	旦	8	ธ์≶ั	14;	19	9=	5		
5	(의	Ξ	-			1		_			_	d	1	IAM98 Workcell Bar Chart				1	П	Т	Т	П	Т	Т	П	1.1				
	Η.	Ē			: 5	1		1	П	H	1	l	l	ပြ				ı				11		1		-				
Tools		_						1					t	ᇒ			١.	4		1	1			R	4 1					
	IEI.	ऴ				1 1	1	-	1 1				밀	Ξ		<u>~</u>		띜			1	ह्न	-	ē						ö
111	17	돈				5		200	188	8	₩		ပြ	ဒ္ဓ		슅		2		- 1		늶		18	1 1					달
	ल	9		⊴	4	Gripper	1	4502A	5508B	5509A	32 bA 55 68		قِ	हि		Se		ই	ارا	8	1	S.	واي	신	واررا	9				8
Build	[일:		ου	Ď	ÖÇ	ō						ll	별	≥		4	. اعا	1]	stclamps	ndclamps	عام	ğ	팀	Alder-Col	stclamps	sudpu	<u> </u>		1	!!
		8	Ę	Ç.	تأت	호	OWN,	86	35	8	팀은	H	먎	lω		豆	固		ē	뀰	Scator	돃	읭	318		雪	Stpins	9		ន្ត
1 1 1	Mechanical	IAM98	Resource	Pin 2504	PIN 5502A	Robot	∄,		Camp	Clamp	S S S S S S S S S S S S S S S S S S S		Control Bar Chart	ĮΞ		Control Assembly	Sudplus		띪	Ħ	ocators	Operator-Station	Stdclamps	Velder-Controller	اڭا:	15	St	dumps		ည
	. ≥ :	⊻	œ					_1_		<u> </u>		V	ပ	≤		O	2.21	2=		. 9	1		1	15	<u></u>	T	_1	_	V	10
Project		4							٦		0	1	Γ	ब					Т		\neg	_		5	<u>:</u>			Þ		cal Resources it controls
ام		_	w.w		ທຸທ	·.						Δ	r	-							\neg	:			ation				Δ	2
1 1	41			٠,	220	,'							ı								ı	nts	ç	 2013	a 45	ı				ca
8	4	ì	عق		2	:						\vdash		1							1		=	3 2	3 5	l			Н	iu
Add	11		ក្តក្ន	•	56	5						1						_		ē	1	5	: 8	2 P	_ 	1			ı	ha
	S		ຂະ		SE	•						1					<u>a</u>	_	N	<u>8</u>	-	믬	ပ္ဆဲ့ န	בַּׁ.בַ	7 7	1				မြ
	Resources	•	ProximitySensor PP1		ProximitySensor PP ProximitySensor PP	3	•	<u> </u>									5	Gripper-Controller	Gripper-Controller2	E		Compone	Logic	Diagriconico Wiring Diagram	Document	1				Σ
≥	겲	:	들듣		<u> </u>	ີ ເກີ	7	₹⋖	ω	4 (ַ מַ		ş	S			Ü	2	2	ರ	· L	끄			٠ ـ	J				9
View	되었	р 	듯듯	0.	产은	Ğ,	ള	14	7	9	35151 4502		읔	富	ب		Ÿ	ĭ	Ĕ	g	ທ [ູ] ່	3 %	Š			-				₽
	وإعما	, st	55	15	<u> </u>	ğ:	늏	386	35	ន្តិ	ე გ		Ĭĕ	Ę	등	5 1	₹ 8	\	ಧ	Ę,	o IstClamps		ם	-	[v	ीस (γ 2 .	- }		g
		کي ر	<u>ــالــ</u> 1	2	٣٠	를	<u>a</u> 5	ם מ	. 0	ے	م م	1 1	ĕ	SS	es d	34	3	e -	9	쑬	ج ج ھ	<u> </u>	<u>a</u>		SIE	ĮŽ.	ot d	8		ä
Ē	計			ø	ı	5	≥ ;	υĒ	Ē	E	ĒĒ		Ľ	≤	ڄ٥	γú	ήŠ	8	ā	φ̈́ (5	강유	ပ္	to i	三性	ie.	<u> </u>	E		2
1 1 1	92	3 5	I	Ę	I	8	ይ :	38	8	ဦး	Cland		浧	2	±º	Ĺ	<u> </u>	5	3	<u>ф</u>	ន្ត្រ	38	#	હેં:	o IstPins	18	DumpSet	리		ā
ile Edit	Vechanica	Vorkveir IAM 90 D Fixture Nest 1		Fixture	نـــ	2	2	D Clamp 3514A	Ö	0	0 0		Control Resources	Control Assemblies	D Part-Present		DNachiSA160-controller	Ō	ŏ.	OSafe-BulkheadClampSet	ם כ	ם כ	04thClamps	ا يَة	ع م	□ LocatorSe	ົ້ວັ	ODumps ODumps		2ndPins and the Mechan
읊	†≥ l3	žο		0			E	3				₹	Ö	Ö	0		0			0				0		0	0		V	7
								-					_					_												


									•								
×	1	T			P	4										7	
a		25 (8)	2				-	123	\mathbf{II}	\prod	\prod	Π	Π				
H		ត្រោ				2	91		+	+	$\perp \perp$	\Box		2 22 22 2	2 C	\mathbf{H}	
H		Sycle Time 192.0 Secs	3			l ₽	Cycle Time	S		11	11		N			Ш	
	jo			IIII		12										11	ļ
	je .				- 11 - 1	ج	릤	\Im	11		11		劉				
	ē,	×911			- 11 - 1	Ĭ	اجرا	92.0	1.1		11	H				11	1
	(S) Operator			1111	-		J	$\Pi \otimes \Gamma$			11:	11	3			11 1	ı
111				1111	- 11	7	į						翼				
	11					[₹	·	H			11	П	図				1
	ಠ			1111	-	I≥							WANE AND AND AND AND AND AND AND AND AND AND				ı
	胚型Robot	夏 夏			1							88			11:	11	ı
					11 1	ه ا	,		Π	П	一段		П	3.1			1
111				1111	- !! !	골					第八年八年	1					1
	11				11 1	ΙĔ						1 l	11				1
	l je		88.50	323	ᆐ	I E		11	1-6	S 8		- -	╀	- -	H		
	ľĚ	25 23 2 27 27 2	TX T	120	" 	ğ)		EST ST	1		\vdash	╁┼	+++	╫┼┤		1
	底器 Mechanical			+++	41 1	語 Physical 配置 Programmable 回りけual 配置 Conditional			<u> </u>				$oldsymbol{\sqcup}$	13	$\sqcup \sqcup$	11	I
	1 8				11 1			2000									I
						153											I
Help	図	383		HHH	41 1	ह			11	$\sqcup \bot$	H		Ш		\Box		ı
ᅵᅵ피		1 com	<u>a </u>	Щ	47	1.8				Щ.	لللل	ш	Ш.			H	L
111	lε	医			71	듄		a	1	П			П				İ
	<u>ē</u>	医 菌素				8		. I S	3		le je						l
18	2 g					183	S	Į	11				o l				ı
1 5	<u>6</u> 0	Activity Fixture Fixture	ixture ixture	xture	ואנת		Reduest	ext Load-Cycle	XX	X X	ext Load-Part	XX	Weld	5000 5000 5000 5000 5000 5000 5000 500	<u> </u>		ł
Window	Mechanical Timing Diagram IAM98 Workcell Timing Diagram	≪ minin	1-1-1-1	minimin	4	늘	œ	FAIT	9 0	[[]		का का	75	1500	25		ı
	히훈				71	١Ë					П			<u> </u>			ı
<u>. \o</u>	lod i=		1			٦											ı
Tools	티듬]			چ کے					ΙЫ		er2			S	ı
-	티호			0	7 j	텏킇	숦	Ϋ́			[5	11	픩			2	ı
		444	Robot Gripper Dumo Clamp 2506A Clamp 4502A	5508B 5509A 5516A	레 17	길본	Control Assembly	2ndbins Sripper-Controller			cators perator-Station	1 }	Velder-Control stclamps		- 1 11	重	l
Build	≌ ≯	2504A 5502A 5508A 5508A	高 23 4	2000 L	3 6	3 8	ŞŞ	ြုဒို	S	g		ଅଧ	ସ୍ଥନ୍ନ	8		8	l
	[등] 🕉			واطواد	4 7	51~	_ =	티칠함	ΝĒ	둳	띩읦	틺틺	위틸	티얼의	엁제	=	ĺ
111	민은	28 1-1-1-	Sobot Clamb Clamb Clamb		$\parallel - \parallel \stackrel{\circ}{\cdot} \parallel$	100	눝	Zndoins Gripper-	dumps Istclamps	Indelamos stoins	ocators Derato	ordiciamps officiamps	Velder-Cost stclamps	rdclamos ndpins stoins	dumps		ı
팅	Mechanica IAM98 Wo	है विवर् व			4	IAM98 Workcell Bar Chart	පි	NO	d'S	<u> </u>	₽Ö	24	≯જ	22	희레	취림	ĺ
Project	1			7	┵╌┦╌	-										귀힜	l
۵		000	~~~ <u>~</u>	11	4	101								· ·	ᆜ의	Resources it controls	l
		P1.s 22.s 22.s	ŧ	•		1.									ļ		l
06		لط مُرَّمُ			Ш										ı	1.21	
Add		 35 55				1		•		**					1	그림	ĺ
	5	STS TSC TSC TSC						<u>a</u>		တ္ထိ					1	딩	ŀ
114	Resources 198 st 1	နိုင္ကို လွိုလ္ခ်ိဳ	<u>e</u>			1		53	67. 67.	Ē					ļ	Mechan	i
	3 4		SX XX	m v a	a	8		T T	ਰੋ ਚੋਂ	<u>8</u>					1		[
View	S	즐물~들들	S. S. T.	4886	1 19	<u>ا</u> ھُا}		٢			လ လ	S			į	the state of the s	l
1 1 14	St SE	Fixture Nest 2 ProximitySensor PP1_s ProximitySensor PP2_s ProximitySensor PP2_s	영영	35148 5516A 5516B 4502	֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓		<u> </u>	≓ශ්ර	Gripper-Controller	Safe-Bulkhez 1stClamps	CandClamps SadClamps	O 4thClamps PinSet	۲.	٠٠ ١ ١	- 1	Ы	!
Edit	BES.	TEA.		222	يًا ا	SS	353	₹ ₹ ;		픚틊	필드	an	ည	# S &	اي تو	læ	
	ਕੂੜ e	اوا	E SE			هکٍا	9	1 S	육준	ಥೆಪ	유호	ᅙᇷ	ā P	설환회	132	2	
	ÄÕ∄	§	နှုန်ခွဲခွဲဗွဲ			12 :		ក្ខភ្ជុ	55.	हैं इ	22	₩	o IstPins	Locatorset Clocators		등	
File Edit Vi	Mechanical Re WorkCell IAM98 © Fixture Nest 1	ر بر القرار الم	Robot Gripper05 Robot Welding04 D Fixture Easel Fixture D Clamp 3514A	000		Control Assemblies	o PP-Otrort	DNachiSA160-controll	o o	DSafe-BulkheadClampSet C1stClamps	00	a 4thC	ם ל	Cocatorse Clocators		2ndPins and	
	<u>> 0 </u>	0	u		₽			U	, 1	J		U		a (401	

×	11 11	D		
				1
Heip	(2) Cycle Time Cycle Time Cycle Time Cycle Time 192.0 Secs - 192.0 S	XX	Programmable Colvirual Colondition Cycle Time (92.0 Secsion of the colondition of the c	
Window He	V 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	rixture	Request Extra Physical Extra Ext Ext Ext Ext Ext Ext Ext Ext Ext Ext	
Project Build Tools Win	Mechanical Timing Diagram Mechanical Timing Mechanical Timin		ar Charles and the state of the	Resources it controls
P	4	٥		Re
View A	clarical Resources control Resources control Resources control Resources clarical Resources contro	a Clamp 4502	Resourcesell stands of the sell	2ndPins and the Mechanical





	4			٥		0	4						4
act Build Tools Window Help	View Go Favorites Help		☐ D:\cpga\EcOLatest\Doc\CAcat.html		Assembly name : safe-bulkhead-clamp (Create an instance)		ion: Used to control moving devices when there is a safety requirement of a fail- ve for the extended position of the pneumatic cylinder		1. 2 position double solenoid valve 2. 2 position 4 way single solonoid valve 3 (variable number) programatic cylinder with concern for cylinder with	lable fruitbert pricuriation of the sensors for extended and retracted positions		> <u> </u>	D
Add Project Internet Explorer	Edi	₹ -	Address	Control Assembly Catalog		Code: SBC	Description: Used safe valve for the	Components:	1. 2 position de 2. 2 position 4 3 Avariable pur	Actions:	Extend Retract	▽	Δ
File Edit View	WorkCell IAM98	Proxim Proxim	Proxim Proxim	Robot Gripper05 Robot Welding04 © Fixture Easel Fix	O Clamp 3514A O Clamp 3514B O Clamp 5516A	Clamp 5516B Clamp 4502		DPP-Extort	Gripper-Contr Gripper-Contr Safe-BulkheadC D1stClamps	a 2ndClamps a 3rdClamps a 4thClamps	D 1stPins D 2ndPins D LocatorSet	aDumpSet aDumps	₹






FIG. 81




FIG. 82





FIG. 83







FIG. 85A









FIG. 87


-		ſ-	3523		h b	.Q.					1CT	RACT"		<u> </u>		į.	
	3504			_	FEXT: "TWO-POSITION VALVE EXTEND"	iext: "Spring-return valve extend"	fext: "1st cylindicator extend"	FEXT: "2ND CYLINDICATOR EXTEND"	FEXT: "3RD CYLINDICATOR EXTEND"	TEXT: "4TH CYLINDICATOR EXTEND"	TEXT: "TWO-POSITION VALVE RETRACT"	iext: "Spring-return valve retract"	TEXT: "1ST CYLINDICATOR RETRACT"	TEXT: "2ND CYLINDICATOR RETRACT"	TEXT: "3RD CYLINDICATOR RETRACT"	TEXT: "4TH CYLINDICATOR RETRACT"	
٠.	٠		ACTIVITY		TEXT: "TWO-	TEXT: "SPRII	TEXT: "IST (TEXT: "2ND	TEXT: "3RD	TEXT: "4TH	TEXT: "TWO	TEXT: "SPRII	TEXT: "IST	TEXT: "2ND	TEXT: "3RD	TEXT: "4TH	
				<u>∞</u>	1	1	1	ı	ı	0	ı	1	t	1	1	-	
	•			1	1	1	1	ŧ	1	_	1		1	ı	.1	0	•
	က		_	9	1	ı	i	ι	0	1	ı	ī	ı	ı	_	,	•
-3501	3503			ਨ.	1	1	ţ	ı		1	ŧ	1.	1	ı	0	1	7 A
\tilde{J}		APS)		14	1	1	1	0	1	ı	1	1	1		ı	1	∞
	*	CLA		13	ı	1	1	-	ı	i	1	ı	ŧ	0	1		FIG. 87A
		(1ST		12	ı	1	0	1	t	1	ı	1	-	1	1		
		TION		=	1	ŧ	_	1	1	ı	1	ı	0	1	ı	1	
		IFICA.		9	ŧ	_	ı	1	1	1	1	0	i	1	ı	٠	
		SPEC	507-	02	ı	_	i	1	1	ı	ı	0	1		ı	1	
		TICS	_T 350	94	0	ŧ	ı	ı	ı	ı	_	ŧ	1	1	1	•	
•		GNOS	MEN	03	0	ı		ı	ı	ı	_	1	1	ı	1.	,	
		DIA	REQUIREMENT	05	_	ı	1	ı	1	1	0	1	1	t		1	
		ASED	Ř	2	7	(1	()	(1	1	ŧ	9	1	ı	1	ı	'	
		STATUS BASED DIAGNOSTICS SPECIFICATION (1ST CLAMPS)	REQUEST		EXTEND	- 1	3520	7	7	7	RETRACT	7		9	7	9	/ 9486g
		2505		3515 -	3511~	9480g	•	9482g+	9484g	9486g -	3513~	3521 9480g		3462g-	94846	2	


FIG. 8/A


























FIG. 96







BACK NEXT FINISH CANCEL

7125-

I2 PASSIVE L

FIG. 100

CYLINDICATOR

RETRACT 1ST


CYLINDICATOR

7601

-7127

TEXT: "SENSOR ERROR"

7109









FIG. 103










		·								
CODE BUILDING 8023	TABLE 025	802	6 8027							
CA TYPE REQUEST	CODE	CODE)	PARAMETERIZIN	RIZING RULE SET (PRS)						
PART-PRESENT			8201 8207							
NACHISA160-CONT.	• • •		8203	822						
SAFEBULKHEADCLAMPS -EXTEND 8029	CODE	PLC I/O TABLE	PARAMETER FLAGGED BOX	CODE MODIFICATION CLOSE SWITCHES	PLC 1/0 TABLE MODIFICATIONS ADD 05; 06					
8033	8032 8060 – 2731 –	8209	9480a FLAGGED BOX 9490	CLOSE SWITCH	ADD 1ST CLAMPS EXTEND REQUEST CONTROL					
			:	8215 : 8217						
8035 	8115				8301					
-RETRACT	CODE		PARAMETER	CODE MODIFICATION	PLC 1/0 TABLE MODIFICATIONS					
8038	8034									
-MANUAL 8012	CODE		PARAMETER	CODE MODIFICATION	PLC 1/0 TABLE MODIFICATIONS					
PINSET					2202					
LOCATOR SET	• • •			•••	8303					
:				•						

FIG. 106









40)]
	40

		8411 840	5	8417	8407						
HMI BUILDING TA	ABLE	8413	8725	5	8419	8735					
8403	MONITORABLE (INDICATORS) CONTROLLABLE (BUTTONS)										
CA TYPE	1/0	LABEL	LINK TO	1/0 REQ	LABÉL	LINK TO					
PART-PRESENT		• • •			•••						
NACHISA 160-CONT.	• • •	• • •			•••						
SAFEBULKHEADCLAMP SET 8727 —	01	2-POSITION VALVE HOT EXTEND OUTPUT	"NAME" 01	01	2-Position valve hot extend	"NAME" 01 CONTRO					
8029 8729—	02 : :	2-POSITION VALVE COMMON EXTEND OUTPUT	"NAME" 02 :	02 :	2-POSITION VALVE COMMON EXTEND :	"NAME" 02 CONTROI					
8731	11	1st cylindicator Extend Signal	"NAME"]]	extend	extend	"NAME" EXTEND REQUEST CONTROL					
8733	<u>I2</u>	IST CYLINDICATOR RETRACT SIGNAL :	"NAME" i2 :	RETRACT	RETRACT	"NAME" RETRACT REQUEST CONTROL :					
·											
PIN-SET											
:	:	:		:	:						

FIG. 110








FIG. 112





FIG. 113








FIG. 116













FIG. 121

























Fig. 128














Fig. 132